Sockets

Female headers were designed for connecting with Wire-Wrap pin headers with square cross-section of 0,635x0,635mm.

Pitch 2,54mm

Single-row, heigth 5,5mm Female headers for connecting with Wire-Wrap pin headers. Dimensions: H=5,5mm, C=3mm. Female sockets can not be broken into smaller sections. Plating: "G" - gold - flash, "Z" - tin.



	Part No.	Ord.No.	Description
s	BL1X05G-ST5,5	6894	1x5 RM2,54 Au
s	BL1X10G-ST5,5	65499	1x10 RM2,54 Au
s	BI 1X207-ST5 5	20075	1x20 BM2 54 Sn

Single-row, heigth 8,5mm

Female headers for connecting with Wire-Wrap pin headers. Dimensions: H=8,5mm, C=3,2mm. Plating: "G" - gold - flash, "Z" - tin. Female sockets can not be broken into smaller sections.



Double-row, heigth 8,5 mm

Double-row female headers for connecting with Wire-Wrap pin strips. Dimensions: H=8,5mm, C=3,2mm. Plating: "G" - gold - flash, "Z" - tin. Female sockets can not be broken into smaller sections



	Part No.	Ord.No.	Description
s	BL2X05G-ST8,5	47322	2x5 RM2,54 Au
s	BL2X10G-ST8,5	8193	2x10 RM2,54 Au
s	BL2X20G-ST8,5	45211	2x20 RM2,54 Au

Single-row, heigth 8 mm

fircher elektronik 🛛 🗏

PCB female headers with straight pins, strips may be broken into smaller parts. Plating: "G" - gold - flash, "Z" - tin.



ouble-row, heigth 8mm

fircherelektronik

PCB double-row female headers with straight contacts, strips may be broken into smaller parts. Plating: "G" - gold - flash.






	Part No.	Ord.No.	Description
s	BL2X17G-SO8	5175	2x17 RM2,54 Au
s	BL2X20G-SO8	8194	2x20 RM2,54 Au
s	BL2X36G-SO8	3629	2x36 RM2,54 Au

Single-row - angled, heigth 8mm

fircher elektronik 🔡 🗏

PCB single-row (BL3) and double-row (BL4) with angled contacts female head-ers, strips may be broken into smaller parts. Plating: "G" - gold - flash.





	Part No.	Ord.No.	Description
s	BL1X20G-SO8-90	8195	1x20 RM2,54 Au
s	BL2X20G-SO8-90	8196	2x20 RM2,54 Au

Pitch 2,54mm - precise

Single-row, heigth 3,6mm

Precise PCB single-row female headers with straight gold-plated contacts mating with SPL series pin headers. Strips may be broken into smaller parts.



1	1		1
17	e	H	3,6
7,4	-1-	ų,	
1 1			v Ø 0,53
			2,54

	Part No.	Ord.No.	Description
s	BL1X20G-PSO4,1	13275	1x20 RM2,54 Au
s	BL1X32G-PSO4,1	13276	1x32 RM2,54 Au
s	BL1X64G-PSO4,1	24767	1x64 RM2,54 Au

Single-row, heigth 7 mm Precise PCB single-row female headers with straight gold-plated contacts mating with 0,635x0,635mm pin headers as well as with round pin headers with max. 0,85mm cross-section. Strips may be broken into smaller parts.



Double-row, heigth 7 mm Precise PCB double-row female headers with straight gold-plated contacts mating with 0,635x0,635mm pin headers as well as with round pin headers with max. 0,85mm cross-section.

00000				6.1 7.0 6.1 3.0 0.6 1 7.0 3.0 2.54		
		Part No.	Ord.No.	Description		
	s	BL2X20G-PSO7	8197	2x20 RM2,54	Au	
	s	BL2X36G-PSO7	4427	2x36 RM2,54	Au	



E