


LCD/OLED modules




BC0802B



BC1602L



BC2002A



BC2004B




BO12832A




BO9864B



BG12864A



BG320240F



BL12864G

Model	Format	Outline Size [mm]	View Area [mm]	Dot/Char size [mm]	Controller	Back Light	Touch Panel
BC0802B	8*2	40*20	36.3*13.9	3.12*5.01	KS0066	LED	-
BC1602L	16*2	68*26.8	61*19	2.96*6.68	KS0066	LED	-
BC2002A	20*2	116*37	85*18.6	3.20*5.55	KS0066	LED	-
BC2004B	20*4	146*62.5	123.5*43	4.84*9.22	KS0066	LED	-
BO12832A	128*32	82*34	79*24.2	0.53*0.59	P C F 8 5 3 1	LED/EL	-
BO9864B	98*64	34*34	31*22.5	0.26*0.31	ST7548i (I2C)	LED/EL	-
BG12864A	128*64	93*70	72*40	0.48*0.48	KS0107/0108	LED	NO
BG320240F	320*240	166.8*109	122*92	0.34*0.34	RA8835	CCFL	YES
BL12864G	128*64	76.65*52.7	60.0*32.5	0.40*0.40	5501303	OLED	-

TFT/ Embedded modules



BT3.5BACHB

Format: 480*234 (3.5")
 Outline Size: 83*60.5mm
 View Area: 72*50.6mm
 Back Light: LED
 Inputs: CVBS/S (NTSC/PAL)



BT104BBBACH352e

Format: 800*600 (10.4")
 Outline Size: 236*174.3mm
 View Area: 211.2*158.4mm
 Back Light: CCFL
 Inputs: CVBS (NTSC/PAL/SECAM),
 VGA



BEGA220

400MHz 32 bit RISC architecture
 ARM926EJ CPU core
 2GB NAND Flash / 64MB DDRII memory
 WINCE 5.0 OS
 Maximum 16M color at 24bpp
 On board 10 / 100Mbps Ethernet with RJ45
 1 x Host USB / 1 x Device USB
 1 x isolated RS485 / 422
 3 x RS232 / 1 x SPI
 Audio codec with dual channels amplifiers
 6 x Channels ADC, one 4-wired touch panel
 12 programmable IO
 Dimension(WxHxD):195x110x25.7 mm

BOLYMIN INC.

5F, 38 Keya Rd. , Daya Township, Central Taiwan Science Park,
 Taichung County, Taiwan 42878, R.O.C.

info@bolymin.com.tw

www.bolymin.com.tw

Displays for your applications