



















Product overview

1-phase AC filters / DC filters

Filter type	Rated voltages	Current range 0 60 A	Application				Attenuation				Leakage current				Connection				
			General purpose	Industrial	Medical	IT / Telecom	Standard 20 - 50 dB	High 40 - 70 dB	Very high 60 - 80 dB	Excellent > 70 dB	Medical < 5 µA	Medical < 80 µA	Standard < 0.5 mA	Industrial > 0.5 mA	PCB	Quick connect	Bolt and nut	Screw terminals	Wire leads
Single stage filter																			
	5500 optional shield	125 VAC 250 VAC	1 - 10 A	•	•			•				•	•		•				
	FMAB-72 aluminium shield	125 VAC 250 VAC	2 - 16 A	•	•			•				•	•	•	•				
	FMLB-09 /-41 /-51 cost optimized	125 VAC 250 VAC	1 - 20 A	•	•	•		•				•	•	•	•		•		•
	FMW-41 optional surge protection	125 VAC 250 VAC	1 - 10 A	•	•	•		•				•	•	•	•		•		•
	FMW-55 for industrial application	125 VAC 250 VAC	10 - 20 A	•	•			•						•	•		•		
	FMAB broad band attenuation	125 VAC 250 VAC	12 - 30 A	•	•	•		•	•					•			•		
	FMAB NEO high symmetrical attenuation	125 VAC 250 VAC	1 - 60 A	•	•	•	•			•	•	•	•	•	•		•	•	•
	FMAB CEE CEE connector	125 VAC 250 VAC	16 - 32 A	•	•			•						•			•		
	FMAB RAIL DIN rail mounting	125 VAC 250 VAC	10 - 20 A	•	•			•	•					•			•		
	FMEB / FMEC DC single and dual pole	80 VDC	5 - 30 A				•	•				n/a		•		•			
Double stage filter																			
	FMBB broad band attenuation	125 VAC 250 VAC	8 - 25 A	•	•	•				•				•	•		•	•	
	FMBB NEO broad band attenuation	125 VAC 250 VAC	1 - 36 A	•	•	•		•	•			•	•	•	•		•	•	•
	FPBB RAIL overcurrent and over-voltage protection	250 VAC 250 VDC	1 - 16 A	•	•	•	•			•				•	•				•
	FMBB RAIL DIN rail mounting	125 VAC 250 VAC	1 - 10 A	•	•			•	•					•	•		•		
	FSW high asymmetrical attenuation	125 VAC 250 VAC	3 - 36 A	•	•			•						•	•		•	•	
	FSS high symmetrical attenuation	125 VAC 250 VAC	1 - 10 A	•	•			•						•	•		•		•
Multi stage filter																			
	FMW-150 high attenuation	125 VAC 250 VAC	4 - 30 A	•	•			•	•	•				•			•		

3-phase AC filters / DC filters

Filter type	Phases neutral	Rated voltages	Current range	Application				Attenuation				Leakage current			Connection			
				General purpose	Drives	Industrial	Renewable energy	Standard 20 - 50 dB	High 40 - 70 dB	Very high 60 - 80 dB	Excellent > 70 dB	Standard < 1 mA	Industrial < 15 mA	Industrial > 15 mA	Quick connect	Bolt and nut	Screw terminals	Bus bar
Single stage filter																		
 FMAC NEO compact design	3P	520 VAC	16 - 230 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAC wide current range	3P	480 VAC 520 VAC	6 - 1100 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAC ECO cost optimized	3P	480 VAC	16 - 150 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAC RAIL DIN rail mounting	3P	480 VAC	3 - 20 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMW4-65 compact design	3P N	440 VAC	3 - 20 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAD high attenuation	3P N	277 VAC 480 VAC	6 - 250 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAD CEE CEE connector	3P N	415 VAC 480 VAC	16 - 32 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAD RAIL DIN rail mounting	3P N	277 VAC 480 VAC	3 - 20 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMER SOL high power DC photovoltaic Filter	2P	1200 VDC	25 - 2300 A	•	•	•	•	•	•	•	•	n/a	n/a	n/a	n/a	•	•	•
Double stage filter																		
 FMBC ECO cost optimized	3P	480 VAC	10 - 115 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMBC NEO light weight	3P	480 VAC 520 VAC	7 - 180 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMBC LL low leakage currents	3P	520 VAC	7 - 180 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMBC BOOK STYLE slim design	3P	480 VAC	10 - 115 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMBD NEO excellent performance	3P N	300 VAC 520 VAC	8 - 200 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Multi stage filter																		
 FMCC SOL compact for high power	3P	520 VAC 760 VAC	150 - 2500 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Output filter																		
 FMAC OUT high voltage	3P	550 VAC	8 - 32 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
 FMAC SINE / DCL optional version DCL	3P	500 VAC 288 VAC	4 - 16 A	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Web Information

At schurter.com you can enter the filter type (e.g. FMBB) into the search box and download the data sheets containing all relevant details.



Customized Solutions

In addition to its broad product range, SCHURTER also offers measurement services to ensure all customer requirements for EMC compliance. We will also build specific samples and provide you with your individual EMC solution. schurter.com/emc-service

